



## AGP



### DM12 - WET DRILLING



- Heavy duty drilling applications - wet core drilling only
- Highly efficient 2800W motor
- 3 Speed motor
- Up to 350 mm diameter wet cores
- For rig mounted drilling only
- Slow start automatic function to protect core segments
- Aluminium housing for cooling and durability
- Horizontal and vertical spirit level for accurate set up
- Internal management system controls amount of power applied
- LED for overload alert & Anti seize ring for core drill connection
- 2-in-1 spindle - 1 1/4" UNC (M) & 1/2" BSP (F)
- Oil bath gearbox & mechanical clutch
- Brushed motor

### TECHNICAL DATA

	DM12
Voltage	110-120V ~ 50-60Hz
Input Power	110-120V : 2800W
Max Core Diameter	350 mm
Collar Diameter	60 mm
No-Load Speeds	350 (#1), 600 (#2), 1000 (#3)
Rated Load Speeds	220 (#1), 370 (#2), 620 (#3)
Weight	12.9 kg
Dimensions	550 mm x 155 mm x 210 mm
Vibration Level	<1.5 m/s <sup>2</sup>
EAV / ELV / Exposure Points (P/H)	EAV - 22 hrs 13 mins · ELV - >24H · EP/H 5
Decibel Level	97.0 dB (A)
Oil Type	90W with 625ml capacity
Cord Length	3m